

## 100G EDR QSFP28 Active Optical Cable Transceiver

### Features


- Four-channel full-duplex active optical cable
- Multirate capability: 10 Gb/s to 28 Gb/s per channel
- QSFP28 high-density form factor
- Reliable VCSEL array technology using multimode fiber
- Round OFNP-rated cable
- Hot Pluggable
- Low power dissipation: <3.5W per cable end (<2.5W with CDRs off)
- Commercial operating case temperature range: 0°C to 70°C
- UL certification optional cables
- RoHS-6 Compliant

### Applications

- Infiniband 4xEDR, 4xFDR, 4xQDR
- 10/25/40/100G Ethernet
- 4G/8G/16G/32G Fibre Channel
- SAS3
- Proprietary HPC Interconnections



### QSFP28 Pin Descriptions



Pin	Symbol	Name/Description	Notes
1	GND	Ground	1
2	Tx2n	Transmitter Inverted Data Input	
3	Tx2p	Transmitter Non-Inverted Data Input	
4	GND	Ground	1
5	Tx4n	Transmitter Inverted Data Input	
6	Tx4p	Transmitter Non-Inverted Data Input	
7	GND	Ground	1
8	ModSelL	Module Select	
9	ResetL	Module Reset	
10	Vcc Rx	+3.3V Power Supply Receiver	
11	SCL	2-wire serial interface clock	
12	SDA	2-wire serial interface data	
13	GND	Ground	1
14	Rx3p	Receiver Non-Inverted Data Output	
15	Rx3n	Receiver Inverted Data Output	
16	GND	Ground	1
17	Rx1p	Receiver Non-Inverted Data Output	
18	Rx1n	Receiver Inverted Data Output	
19	GND	Ground	1
20	GND	Ground	1
21	Rx2n	Receiver Inverted Data Output	
22	Rx2p	Receiver Non-Inverted Data Output	
23	GND	Ground	1
24	Rx4n	Receiver Inverted Data Output	
25	Rx4p	Receiver Non-Inverted Data Output	
26	GND	Ground	1
27	ModPrsL	Module Present	
28	IntL	Interrupt	
29	Vcc Tx	+3.3V Power supply transmitter	
30	Vcc1	+3.3V Power supply	
31	LPMode	Low Power Mode	
32	GND	Ground	1
33	Tx3p	Transmitter Non-Inverted Data Input	
34	Tx3n	Transmitter Inverted Data Input	
35	GND	Ground	1
36	Tx1p	Transmitter Non-Inverted Data Input	
37	Tx1n	Transmitter Inverted Data Input	
38	GND	Ground	1

### General Product Characteristics

Form Parameter	Value	Unit	Notes
Module Form Factor	QSFP28		
Number of Lanes	4 Tx and 4 Rx		
Maximum Aggregate Data Rate	103.12	Gb/s	112.02 Max. Aggregate Data Rate with BER 10 <sup>-6</sup> (per 32G Fibre Channel)
Maximum Data Rate per Lane	25.78	Gb/s	28.05 Max. Data Rate per Lane with BER 10 <sup>-6</sup> (per 32G Fibre Channel)
Standard Cable Lengths	1, 3, 5, 10, 15, 20, 30, 50, 100	meters	Other lengths may be available upon request
Protocols Supported	Typical applications include InfiniBand QDR/FDR/EDR, 10/25/40G/100G Ethernet, 4/8/16/32G Fibre Channel, SAS3		
Electrical Interface and Pin-out	38-pin edge connector		Pin-out as defined by SFF-8679
Standard Optical Cable Type	Multimode round fiber cable, plenum-rated		OFNP, Low Smoke Zero Halogen (LSZH), round fiber cable also available
Maximum Power Consumption per End	3.5 (retimed Tx) 2.5 (unretimed)	Watts	Varies with output voltage swing and pre-emphasis settings
Management Interface	Serial, I2C-based, 450 kHz maximum frequency		As defined by SFF-8636

Data Rate Specifications	Symbol	Min	Typ	Max	Unit	Ref.
Bit Rate per Lane	BR	10.00	25.78	28.05	Gb/sec	1
Bit Error Ratio	BER			10 <sup>-12</sup>		2

Notes:

- Supports InfiniBand QDR/FDR/EDR, 10/25/40/100 Gigabit Ethernet and 8/16/32G Fibre Channel applications but at 28.05 Gb/sec BER is limited to 10<sup>-6</sup>.
- Tested with a PRBS 2<sup>31</sup>-1 test pattern.



## Absolute Maximum Ratings

Form Parameter	Symbol	Min	Typ	Max	Unit	Ref.
Maximum Supply Voltage	Vcc1, VccTx, VccRx	-0.5		3.6	V	
Storage Temperature	TS	-40		85	°C	1
Case Operating Temperature	TOP	0		75	°C	
Relative Humidity	RH	0		85	%	2

Notes:

1. Assumes no mechanical load force on the unit. Ensuring no mechanical load force requires a cable bend radius of >105 mm within 100 mm of either cable end module and >60 mm on the rest of the cable.

2. Non-condensing.

## Electrical Characteristics(EOL, TOP = 0 to 70°C, VCC = 3.135 to 3.465 Volts)

NOTE: The EDR module requires an electrical connector compliant with SFF-8662 or SFF-8672 be used on the host board to guarantee its electrical interface specification. Please check with your connector supplier.

Parameter	Symbol	Min	Typ	Max	Unit	Ref.
Supply Voltage	Vcc1, VccTx, VccRx	3.15		3.46	V	
Supply Current	Icc			1010	mA	
Module total power	P			3.5	W	1,2
<b>Link Turn-On Time</b>						
Transmit turn-on time				2000	ms	3
<b>Input electrical specifications (per Lane)</b>						
Differential Voltage pk-pk				900	mV	
Common Mode Noise RMS				17.5	mV	
Differential Termination Resistance Mismatch				10	%	
Differential Return Loss	SDD22	Per OIF CEI-28G-VSR and CAUI-4 requirements			dB	
Common Mode to Differential conversion and Differential to Common Mode Conversion	SDC22, SCD22				dB	
Common Mode Return Loss	SCC22				dB	
Transition Time, 20 to 80%	Tr, Tf	10			ps	
Common Mode Voltage	Vcm	-0.3		2.8	V	
Eye Width at 1E-15 probability	EW15	0.46			UI	
Eye Height at 1E-15 probability	EH15	94			mV	

Output electrical specifications (per Lane)						
Differential Voltage pk-pk				900	mV	
Common Mode Voltage	V <sub>cm</sub>	-350		2850	mV	
Common Mode Noise RMS				17.5	mV	
Differential Termination Resistance Mismatch				10	%	
Differential Return Loss	SDD22	Per OIF CEI-28G-VSR and CAUI-4 requirements			dB	
Common Mode to Differential conversion and Differential to Common Mode Conversion	SDC22, SCD22					
Common Mode Return Loss	SCC22			-2	dB	
Transition Time, 20 to 80%	Tr, Tf	9.5			ps	
Vertical Eye Closure	VEC			5.5	dB	
Eye Width at 1E-15 probability	EW15	0.57			UI	
Eye Height at 1E-15 probability	EH15	228			mV	

### Notes:

1. Maximum total power value is specified across the full temperature and voltage range.
2. Settable in various discrete steps via the I2C interface.
3. From power-on and end of any fault conditions

## Environmental Specifications

EDR Active Optical Cables have an operating temperature range from 0°C to +70°C case temperature.

Form Parameter	Symbol	Min	Typ	Max	Unit	Ref.
Case Operating Temperature	Top	0		70	° C	
Storage Temperature	Tsto	-10		70	° C	

## Regulatory Compliance


EDR Active Optical Cables are RoHS-6 Compliant.

EDR Active Optical Cables are Class 1 laser eye safety compliant per IEC 60825-1.

Standard fiber cable type is round-section construction, plenum-rated. Other cable types can be supported upon request such as LSZH, round-section construction.

## Mechanical Design Diagram (mm)

The EDR module mechanical specifications are compliant with the QSFP28 transceiver module specifications (as defined in SFF-8661), substituting the MPO12 receptacle with a fiber optics cable connecting both ends.



Unit: mm

	L	L1	L2	L3	W	W1	W2	H	H1	H2
MAX	72.2	—	122	4.35	18.45	—	6.2	8.6	12.0	5.35
Typical	72.0	—	—	4.20	18.35	—	—	8.5	11.8	5.2
MIN	68.8	16.5	118	4.05	18.25	2.2	5.8	8.4	11.6	5.05

### Ordering information

QSFP28-QSFP28-AOC5M	5 meter 100G QSFP28 to QSFP28 Active Optical Cable
QSFP28-QSFP28-AOC7M	7 meter 100G QSFP28 to QSFP28 Active Optical Cable
QSFP28-QSFP28-AOC10M	10 meter 100G QSFP28 to QSFP28 Active Optical Cable
QSFP28-QSFP28-AOC15M	15 meter 100G QSFP28 to QSFP28 Active Optical Cable
QSFP28-QSFP28-AOC20M	20 meter 100G QSFP28 to QSFP28 Active Optical Cable

### Notice:

Performance figures, data and any illustrative material provided in this data sheet are typical and must be specifically confirmed in writing by T-TECH before they become applicable to any particular order or contract. In accordance with the T-TECH policy of continuous improvement specifications may change without notice. The publication of information in this data sheet does not imply freedom from patent or other protective rights of T-TECH or others. Further details are available from any T-TECH sales representative.

### Contact:

E-mail: [sales@t-techvip.com](mailto:sales@t-techvip.com)  
<http://www.t-techvip.com>